

## WallpaperSol Persomural 195

■ matt 3280 - 195 g/m<sup>2</sup>

High Quality non-woven wallpaper coated with a solvent ink compatible inkjet layer, which offers a good colour gamut and high scratch resistance. Due to the properties of this wallpaper, no additional protection is needed and it can be hung with standard non-woven wallpaper paste.

### Applications

- Interior design

### Advantages

- The coating and prints are water-resistant - no liquid lamination required
- Quick dry
- Smooth surface with satin finishing
- Wide gamut and high colour rendering
- High opacity for good coverage
- High dimensional stability and wet strength resistance
- Can be applied with standard paste for non-woven wallpaper
- Can cover small cracks
- Easy to remove
- PVC-free
- [Fire Classification: C-s1,d0 \(ISO EN 13501-1:2007\)](#)

## WallpaperSol Persomural 195

■ matt 3280 - 195 g/m<sup>2</sup>

### List of Printers

| Printer                                                     | Ink                          | Quality   |
|-------------------------------------------------------------|------------------------------|-----------|
| Hewlett Packard DJ L65500 Latex ink                         | Inkjet mit IR- / Latex Tinte | Excellent |
| Hewlett Packard DJ L25500 / 26500 / 28500 - Latex 260 / 280 | Inkjet mit IR- / Latex Tinte | Excellent |
| Hewlett Packard Scitex LX 600                               | Inkjet mit IR- / Latex Tinte | Excellent |
| Hewlett Packard Scitex LX 800 / LX 820 / LX 850             | Inkjet mit IR- / Latex Tinte | Excellent |
| Epson Stylus Pro GS6000 UltraChrome GS                      | Inkjet mit Eco Solvent       | Excellent |
| Epson SureColor SC-30600 / 50600 / 70600                    | Inkjet mit Eco Solvent       | Excellent |
| Roland SolJet SJ540 / SC540 SJ 740 / SC740                  | Inkjet mit Eco Solvent       | Excellent |
| Roland SC-500 Permasol S                                    | Inkjet mit Lösemitteltinte   | Excellent |
| Roland VersaCAMM SP-300i / SP-540i                          | Inkjet mit Eco Solvent       | Excellent |
| Roland VersaCAMM VP-300i / VP-540i                          | Inkjet mit Eco Solvent       | Excellent |
| Roland VS 540 / VS 640                                      | Inkjet mit Eco Solvent       | Excellent |
| Roland CJV 30                                               | Inkjet mit Eco Solvent       | Excellent |
| Roland SolJET PRO4 XR-640                                   | Inkjet mit Lösemitteltinte   | Excellent |
| Océ CS9360 / CS935                                          | Inkjet mit Eco Solvent       | Excellent |

Last update: 01.01.1900

## WallpaperSol Persomural 195

■ matt 3280 - 195 g/m<sup>2</sup>

### Physical Properties

|                             |                    |               |
|-----------------------------|--------------------|---------------|
| Weight (Total) [gsm]        | 195                | ISO 536       |
| Thickness (total) [microns] | 340                | ISO 534       |
| Chromaticity (D65 / 10°)    | L* 97 a*-0,5 b*3,5 | DIN 6174      |
| Opacity [%]                 | 91                 | ISO 2471      |
| Whitiness (CIE, D65/2°)     | 75                 | CIELab System |

### Recommended use and storage

To maintain the high quality of this fleece, it should be stored and converted in a climate of 30 – 65 % relative humidity and at temperatures of 10 – 30 °C (50 – 86 °F).

After pasteing the wall with a standard wallpaper paste, the wallpaper can be hung just like all other fleece wallpapers. Thanks to its structure, it is easy to remove again and requires no additional protection.

The values provided on this datasheet are only for orientation.

Before using our media please check its compatibility for your printer and intended application. Technical specifications are subject to change, therefore we do not take responsibility for any misprints resulting from technically modified inks and/ or printers. 04.06.2012