

# SAFETY DATA SHEET

## European Graphics Antioxidant

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name European Graphics Antioxidant

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Anti-oxidant spray

#### 1.3. Details of the supplier of the safety data sheet

Supplier Aztec Aerosols  
Gateway  
Crewe  
Cheshire  
CW1 6FA  
T+44 (0) 1270 656380  
F+44 (0) 1270 656381  
info@aztecaerosols.com

#### 1.4. Emergency telephone number

+44 (0)7831 300868

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

Classification (1999/45/EEC) Xn;R65. Xi;R38. F+;R12. N;R51/53. R66, R67.

##### Human health

Gas or vapour is harmful on prolonged exposure or in high concentrations. In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.

##### Environment

The product contains a substance which is very toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

##### Physical and Chemical Hazards

Aerosol containers can explode when heated, due to excessive pressure build-up. The product is extremely flammable, and explosive vapour/air mixtures may be formed even at normal room temperatures. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

#### 2.2. Label elements

##### Labelling



Harmful



Extremely flammable



Dangerous for the environment

##### Risk Phrases

R12	Extremely flammable.
R38	Irritating to skin.
R65	Harmful: may cause lung damage if swallowed.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

##### Safety Phrases

A1	Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
A2	Do not spray on a naked flame or any incandescent material.
S2	Keep out of the reach of children.
S16	Keep away from sources of ignition - No smoking.
S23	Do not breathe vapour/spray.

**European Graphics Antioxidant**

S24

Avoid contact with skin.

S29

Do not empty into drains.

S51

Use only in well-ventilated areas.

**2.3. Other hazards****SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS****3.2. Mixtures**

<b>BUTANE</b> 5-10%		
<b>CAS-No.: 106-97-8</b>	<b>EC No.: 203-448-7</b>	<b>Registration Number: Exempt under REACH</b>
Classification (EC 1272/2008) Flam. Gas 1 - H220	Classification (67/548/EEC) F+;R12	
<b>ISOBUTANE</b> 1-5%		
<b>CAS-No.: 75-28-5</b>	<b>EC No.: 200-857-2</b>	<b>Registration Number: Exempt under REACH</b>
Classification (EC 1272/2008) Flam. Gas 1 - H220	Classification (67/548/EEC) F+;R12	
<b>MINERAL OIL</b> 30-60%		
<b>CAS-No.: 64742-65-0</b>	<b>EC No.: 265-169-7</b>	<b>Registration Number: 01-2119471299-27</b>
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.	
<b>PROPANE</b> 10-30%		
<b>CAS-No.: 74-98-6</b>	<b>EC No.: 200-827-9</b>	<b>Registration Number: Exempt under REACH</b>
Classification (EC 1272/2008) Flam. Gas 1 - H220	Classification (67/548/EEC) F+;R12	
<b>White Spirit (Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics)</b> 30-60%		
<b>CAS-No.: 64742-88-7</b>	<b>EC No.: 919-446-0</b>	<b>Registration Number: 01-2119458049-33</b>
Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Classification (67/548/EEC) Xn;R65. N;R51/53. R10,R66,R67.	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

**SECTION 4: FIRST AID MEASURES****4.1. Description of first aid measures**

## European Graphics Antioxidant

### General information

Move the exposed person to fresh air at once.

#### Inhalation

In case of inhalation of spray mist: Move person into fresh air and keep at rest. Perform artificial respiration if breathing has stopped. Keep the affected person warm and at rest. Get prompt medical attention.

#### Ingestion

Immediately rinse mouth and provide fresh air. Do not induce vomiting. Get medical attention.

#### Skin contact

Promptly wash contaminated skin with soap or mild detergent and water. Promptly remove clothing if soaked through and wash as above.

#### Eye contact

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Continue to rinse for at least 15 minutes and get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

### 4.3. Indication of any immediate medical attention and special treatment needed

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

#### Extinguishing media

Extinguish with foam, carbon dioxide, dry powder or water fog.

### 5.2. Special hazards arising from the substance or mixture

#### Unusual Fire & Explosion Hazards

Extremely flammable. Forms explosive mixtures with air. May travel considerable distance to source of ignition and flash back. Aerosol cans may explode in a fire.

#### Specific hazards

Aerosol containers can explode when heated, due to excessive pressure build-up.

### 5.3. Advice for firefighters

#### Special Fire Fighting Procedures

Water spray should be used to cool containers. Use water to keep fire exposed containers cool and disperse vapours. Warn firefighters that aerosols are involved.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. In case of inadequate ventilation, use respiratory protection. Avoid inhalation of vapours and aerosol spray.

### 6.2. Environmental precautions

Do not allow to enter drains, sewers or watercourses. Contain spillages with sand, earth or any suitable adsorbent material.

### 6.3. Methods and material for containment and cleaning up

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb spillage with non-combustible, absorbent material. Let evaporate. Keep out of confined spaces because of explosion risk.

### 6.4. Reference to other sections

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Read and follow manufacturer's recommendations. Keep away from heat, sparks and open flame. Eliminate all sources of ignition. Do not spray on a naked flame or any incandescent material.

### 7.2. Conditions for safe storage, including any incompatibilities

Extremely flammable. Keep away from heat, sparks and open flame. Store at moderate temperatures in dry, well ventilated area. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

### 7.3. Specific end use(s)

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## European Graphics Antioxidant

**8.1. Control parameters**

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
BUTANE	WEL	600 ppm		750 ppm		
ISOBUTANE	WEL	800 ppm		No std.		
MINERAL OIL			5 mg/m3			
PROPANE	SUP	ppm		ppm		
White Spirit (Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics	WEL		600 mg/m3			

WEL = Workplace Exposure Limit.

**Ingredient Comments**

WEL = Workplace Exposure Limits

**White Spirit (Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics (CAS: 64742-88-7)****DNEL**

Industry	Inhalation.	Short Term	Systemic Effects	570 mg/m3
Industry	Dermal	Long Term	Systemic Effects	44 mg/kg/day
Industry	Inhalation.	Long Term	Systemic Effects	330 mg/m3
Consumer	Inhalation.	Short Term	Systemic Effects	570 mg/m3
Consumer	Dermal	Long Term	Systemic Effects	26 mg/kg/day
Consumer	Inhalation.	Long Term	Systemic Effects	71 mg/m3
Consumer	Oral	Long Term	Systemic Effects	26 mg/kg/day

**8.2. Exposure controls****Engineering measures**

Provide adequate ventilation. Observe occupational exposure limits and minimize the risk of inhalation of spray.

**Respiratory equipment**

In case of inadequate ventilation use suitable respirator.

**Hand protection**

Due to the packaging form, aerosol, risk of skin contact is small. Use suitable protective gloves if risk of skin contact. Gloves of nitrile rubber, PVA or Viton are recommended. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

**Eye protection**

Wear approved chemical safety goggles where eye exposure is reasonably probable.

**Hygiene measures**

Wash hands after handling. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Use appropriate hand lotion to prevent defatting and cracking of skin.

**Personal protection**

When using do not smoke.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES****9.1. Information on basic physical and chemical properties**

Appearance	Aerosol.
Odour	Organic solvents.
Flash point (°C)	<-40 °C
Auto Ignition Temperature (°C)	410-580
Flammability Limit - Lower(%)	1.8
Flammability Limit - Upper(%)	9.5
Comments	Information given concerns the major ingredient.

**9.2. Other information****SECTION 10: STABILITY AND REACTIVITY****10.1. Reactivity****10.2. Chemical stability**

## European Graphics Antioxidant

Avoid Heat, sparks, flames.

### 10.3. Possibility of hazardous reactions

### 10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.

### 10.5. Incompatible materials

### 10.6. Hazardous decomposition products

In case of fire, toxic gases (CO, CO<sub>2</sub>, NO<sub>x</sub>) may be formed.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

#### General information

Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.

#### Inhalation

In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Unconsciousness, possibly death.

#### Skin contact

Skin irritation is not anticipated when used normally. Repeated exposure may cause skin dryness or cracking.

#### Eye contact

Spray and vapour in the eyes may cause irritation and smarting.

#### Health Warnings

Arrhythmia, (deviation from normal heart beat). In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

#### Route of entry

Inhalation.

#### Target Organs

Central nervous system Respiratory system, lungs

#### Medical Symptoms

Arrhythmia, (deviation from normal heart beat). Narcotic effect. Vapours may cause drowsiness and dizziness.

## SECTION 12: ECOLOGICAL INFORMATION

#### Ecotoxicity

This product has not been tested but contains ingredients which are toxic or very toxic to aquatic organisms and may cause long term adverse effects in the aquatic environment. During normal use the volatility of the components and the packaging form, pressurised container, make entry into the aquatic environment unlikely, however, do not empty or discharge into drains or watercourses. Ensure container is empty before disposal to prevent contents entering watercourses.

### 12.1. Toxicity

### 12.2. Persistence and degradability

### 12.3. Bioaccumulative potential

### 12.4. Mobility in soil

### 12.5. Results of PBT and vPvB assessment

### 12.6. Other adverse effects

## SECTION 13: DISPOSAL CONSIDERATIONS

## European Graphics Antioxidant

### General information

Do not puncture or incinerate even when empty.

### 13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements. Make sure containers are empty before discarding (explosion risk). Empty containers must not be burned because of explosion hazard.

## SECTION 14: TRANSPORT INFORMATION

### 14.1. UN number

UN No. (ADR/RID/ADN)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950

### 14.2. UN proper shipping name

Proper Shipping Name AEROSOLS (White Spirit (Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics)

### 14.3. Transport hazard class(es)

ADR/RID/ADN Class	2.1
ADR/RID/ADN Class	Class 2: Gases
ADR Label No.	2.1
IMDG Class	2.1
ICAO Class/Division	2.1
Transport Labels	



### 14.4. Packing group

Not applicable.

### 14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant



### 14.6. Special precautions for user

EMS	F-D, S-U
Hazard No. (ADR)	23 Flammable gas.
Tunnel Restriction Code	(D)

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## European Graphics Antioxidant

### Uk Regulatory References

The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments. Chemicals (Hazard Information & Packaging) Regulations.

### Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716). Control of Substances Hazardous to Health. The Aerosol Dispensers Regulations 1977 & 1999

### Approved Code Of Practice

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply. British Aerosol Manufacturers Code of Practice 7th. Edition 1999

### Guidance Notes

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

### EU Legislation

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

### National Regulations

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689.

### 15.2. Chemical Safety Assessment

#### SECTION 16: OTHER INFORMATION

SDS No.	13019
Safety Data Sheet Status	Approved.
Date	23.07.2014
<b>Risk Phrases In Full</b>	
R12	Extremely flammable.
R10	Flammable.
R65	Harmful: may cause lung damage if swallowed.
R38	Irritating to skin.
R66	Repeated exposure may cause skin dryness or cracking.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67	Vapours may cause drowsiness and dizziness.
<b>Hazard Statements In Full</b>	
H315	Causes skin irritation.
H222	Extremely flammable aerosol.
H220	Extremely flammable gas.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.
H411	Toxic to aquatic life with long lasting effects.

#### Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.