

LITHO SUPPLIES (UK) LTD UNIT 1-2 ASHBOURNE COURT ILKESTON, NT DE7 8EF United Kingdom

August 16, 2016

# Save Money! Be Green! Receive MSDS electronically! Email your request to regulatory.emsds@sunchemical.com

Ayez une pensée pour l'environnement ! Gagnez du temps et de l'argent ! Recevez vos FDS par voie électronique! Envoyez vos demandes à regulatory.emsds@sunchemical.com

Ahorra dinero! Cuida el medio ambiente! Recibe las Hojas de Seguridad por correo electrónico! Envoyez vos demandes a regulatory.emsds@sunchemical.com

Sparen Sie Geld! Handeln Sie umweltbewußt! Fordern Sie Sicherheitsdatenblätter in elektronischer Form an. Richten Sie Ihre E-Mail an: regulatory.emsds@sunchemical.com

Risparmia soldi! Sii ecologico! Ricevi MSDS in formato elettronico! Invia la tua richiesta all'indirizzo regulatory.emsds@sunchemical.com

Poupe dinheiro! Seja verde! Receba as F.D.S. electronicamente! Envie o seu pedido para o email regulatory.emsds@sunchemical.com



# **SAFETY DATA SHEET**

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2015/830 - United Kingdom (UK)

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : GS9D400085:SOLAR AQUA 237C PINK:DL02

Product code : GS9D400085

Trade name : SOLARAQUA

Date of issue/ Date of revision : 11 August 2016

Version : 0.01

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses				
Colorant; Printing ink related material; Printing ink.				
Uses advised against Reason				
Not applicable.				

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/ Distributor : SUN CHEMICAL

**ELIZABETHAN WAY** 

MILNROW ROCHDALE LANCASHIRE OL16 4LE

UNITED KINGDOM (44) 1706 889600 SUN CHEMICAL ELIZABETHAN WAY

MILNROW ROCHDALE LANCASHIRE OL16 4LE

UNITED KINGDOM (44) 1706 889600

e-mail address of person responsible for this SDS

: regulatory.affairs@sunchemical.com

#### 1.4 Emergency telephone number

**Supplier** 

**Telephone number** : (44) 870-8200418 (Chemtrec - 24 hours)

Date of issue : 11 August, 2016 Page: 1/12

# **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

**Product definition**: Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Signal word : No signal word.

**Hazard statements** : No known significant effects or critical hazards.

**Precautionary statements** 

Prevention : Not applicable.

Response : Not applicable.

Storage : Not applicable.

Disposal : Not applicable.

**Supplemental label**: Contains 1,2-benzisothiazol-3(2H)-one and 2,4,7,9-tetramethyldec-5-yne-4,7-diol.

**elements** May produce an allergic reaction. Safety data sheet available on request.

2.3 Other hazards

Other hazards which do :

not result in classification

: None known.

# **SECTION 3: Composition/information on ingredients**

Substance/mixture : Mixture

			Classification	
Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре
propane-1,2-diol	REACH #: 01-2119456809-23 EC: 200-338-0 CAS: 57-55-6	2.5 < 5	Not classified.	[2]
2-aminoethanol	REACH #: 01-2119486455-28 EC: 205-483-3 CAS: 141-43-5 Index: 603-030-00-8	1.0 < 2.5	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1] [2]
2,4,7,9-tetramethyldec-5-yne-4,7-diol	REACH #: 01-2119954390-39 EC: 204-809-1 CAS: 126-86-3	0.1 < 0.25	Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Chronic 3, H412	[1]
1,2-benzisothiazol-3(2H)-one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	0.0067835	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411	[1]

Date of issue : 11 August, 2016 Page: 2/12

	GS9D400085			
SECTION 3: Composition/information on ingredients				
	See Section 16 for the full text of the H statements declared above.			

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

#### **Type**

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

# **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give
	anything by mouth to an unconscious person. If unconscious, place in recovery

position and seek medical advice.

**Eye contact**: Check for and remove any contact lenses. Immediately flush eyes with room

temperature water for at least 15 minutes, keeping eyelids open. In case of accidental eye contact, avoid concurrent exposure to the sun or other sources of UV

light which may increase the sensitivity of the eyes.

**Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

**Skin contact**: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognized skin cleanser. Do NOT use solvents or thinners.

**Ingestion**: If swallowed, seek medical advice immediately and show this container or label.

Keep person warm and at rest. Do NOT induce vomiting.

**Protection of first-aiders**: No action shall be taken involving any personal risk or without suitable training.

#### 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 2,4,7,9-tetramethyldec-5-yne-4,7-diol. May produce an allergic reaction.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to medical doctor : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Date of issue : 11 August, 2016 Page: 3/12

#### **SECTION 4: First aid measures**

**Specific treatments** : No specific treatment.

# SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

media

: Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

Unsuitable extinguishing

media

: Do not use water jet.

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Hazardous thermal decomposition products : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

#### 5.3 Advice for firefighters

Special protective actions for fire-fighters

: Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

### **SECTION 6: Accidental release measures**

Due to the organic solvents content of the mixture:

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

#### 6.2 Environmental precautions

Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

## 6.3 Methods and materials for containment and cleaning up

: Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

#### 6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

Date of issue : 11 August, 2016 Page: 4/12

# SECTION 7: Handling and storage

# 7.1 Precautions for safe handling

: Due to the organic solvents content of the mixture:

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits.

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Keep container tightly closed. Keep away from heat, sparks and flame. No sparking tools should be used.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel.

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

# 7.2 Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 5 - 35 °C

Store in accordance with local regulations.

#### Notes on joint storage

Keep away from: oxidizing agents, strong alkalis, strong acids.

#### Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight.

Keep container tightly closed.

Keep away from sources of ignition. No smoking. Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

#### 7.3 Specific end use(s)

Recommendations
Industrial sector specific

Not available.
Not available.

solutions

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values		
propane-1,2-diol	EH40/2005 WELs (United Kingdom (UK), 12/2011).  TWA: 10 mg/m³ 8 hours. Form: Particulate  TWA: 474 mg/m³ 8 hours. Form: Sum of vapour and particulates  TWA: 150 ppm 8 hours. Form: Sum of vapour and particulates		
2-aminoethanol	EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin.  STEL: 7.6 mg/m³ 15 minutes.  STEL: 3 ppm 15 minutes.  TWA: 2.5 mg/m³ 8 hours.  TWA: 1 ppm 8 hours.		

Date of issue : 11 August, 2016 Page: 5/12

# SECTION 8: Exposure controls/personal protection

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

Product/ ingredient name	Туре	Exposure	Value	Population	Effects
		Long term Inhalation Long term Dermal	3.3 mg/m³ 1 mg/kg bw/day	Workers Workers	Local Systemic

#### **PNECs**

Product/ingredient name	Туре	Compartment Detail	Value	Method Detail
2-aminoethanol	-	Fresh water	0.085 mg/l	-
	-	Marine water	0.0085 mg/l	-
	-	Sewage Treatment	100 mg/l	-
		Plant		
	-	Fresh water sediment	0.434 mg/kg dwt	-
	-	Marine water sediment	0.0434 mg/kg dwt	-
	-	Soil	0.0367 mg/kg dwt	-

#### 8.2 Exposure controls

Appropriate engineering controls

: Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn.

#### Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.

Eye/face protection Skin protection

Hand protection

: Use safety eyewear designed to protect against splash of liquids.

: Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

**Gloves** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Body protection** 

: Personnel should wear antistatic clothing made of natural fibers or of hightemperature-resistant synthetic fibers.

Respiratory protection

: If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.

**Environmental exposure** controls

: Do not allow to enter drains or watercourses.

Date of issue : 11 August, 2016 Page: 6/12

# **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state : Liquid. Color : Red.

Odor : Characteristic. **Odor threshold** : Not applicable. Melting point/freezing point : Not applicable. Flash point : >93.3°C (200F)

VOC : 4% : 7 to 8.5 Hq : Lower: 2.6% Lower explosion limit Upper: 17%

**Boiling point** : Lowest known value: 100°C (212°F)

**Evaporation rate** : Highest known value: <1 (water) Weighted average: 0.83compared with butyl

acetate

Upper/lower flammability or

explosive limits

: Not tested

Vapor pressure : 3.2 kPa (23.8 mm Hg)

Vapor density : Not tested Relative density : Not tested Solubility(ies) : Not tested Partition coefficient: n-octanol/ : Not applicable.

water

**Auto-ignition temperature** : Not applicable. **Decomposition temperature** : Not applicable. **Viscosity** : Not tested **Explosive properties** : Not applicable. **Oxidizing properties** : Not applicable.

#### 9.2 Other information

No additional information.

# SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : Stable under recommended storage and handling conditions (see Section 7).

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition

products.

: Keep away from the following materials to prevent strong exothermic reactions: 10.5 Incompatible materials

oxidizing agents, strong alkalis, strong acids. Keep away from water or moist air.

: 11 August, 2016 Date of issue Page: 7/12

# SECTION 10: Stability and reactivity

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# **SECTION 11: Toxicological information**

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 2,4,7,9-tetramethyldec-5-yne-4,7-diol. May produce an allergic reaction.

#### 11.1 Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
2-aminoethanol	LD50 Oral	Rat	1720 mg/kg	_
1,2-benzisothiazol-3(2H)-	LD50 Oral	Rat	1020 mg/kg	-
one				

#### Irritation/Corrosion

Not determined - Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

#### Sensitization

Not determined - Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

#### **Mutagenicity**

Not applicable.

#### Carcinogenicity

Not applicable.

#### Reproductive toxicity

Not determined - Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

#### **Teratogenicity**

Not applicable.

#### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
2-aminoethanol	Category 3	Not applicable.	Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Not determined - Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

#### Aspiration hazard

Not determined - Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Date of issue : 11 August, 2016 Page: 8/12

# **SECTION 12: Ecological information**

There are no data available on the mixture itself.

Do not allow to enter drains or watercourses.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

#### 12.1 Toxicity

2-aminoethanol Acute LC50 >100000 µg/l Marine water Crustaceans - Crangon

crangon - Adult

Acute LC50 170000 µg/l Fresh water Fish - 0

Fish - Carassius auratus - 3.3 g 96 hours

1,2-benzisothiazol-3(2H)-one Acute EC50 4.4 to 4.9 ppm Fresh water Daphnia - Daphnia magna -

48 hours

48 hours

<24 hours

Acute LC50 1.6 to 2.8 ppm Fresh water Fish - Oncorhynchus mykiss

96 hours

#### 12.2 Persistence and degradability

Not available.

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-aminoethanol	-1.31	-	low

#### 12.4 Mobility in soil

Soil/water partition

: Not available.

coefficient (Koc)

**Mobility** : Not available.

#### 12.5 Results of PBT and vPvB assessment

PBT : Not applicable. vPvB : Not applicable.

**12.6 Other adverse effects**: No known significant effects or critical hazards.

# **SECTION 13: Disposal considerations**

Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

For further information, contact your local waste authority.

#### 13.1 Waste treatment methods

#### **Product**

**Methods of disposal**: The generation of waste should be avoided or minimized wherever possible.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of

all authorities with jurisdiction.

#### **Packaging**

Date of issue : 11 August, 2016 Page: 9/12

# **SECTION 13: Disposal considerations**

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

European Waste Catalogue (EWC):

: 08 03 13 waste ink other than those mentioned in 08 03 12

Special precautions

: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.3 Transport hazard class(es)	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	-	The product is only regulated as a dangerous good when transported in tank vessels.	-	-

14.6 Special precautions for user

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

: Not available.

# SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Substances of very high concern

None of the components are listed.

Date of issue : 11 August, 2016 Page: 10/12

GS9D400085

# SECTION 15: Regulatory information

**Annex XVII - Restrictions** 

: Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

Industrial use : The information contained in this safety data sheet does not constitute the user's

own assessment of workplace risks, as required by other health and safety

legislation. The provisions of the national health and safety at work regulations apply

to the use of this product at work.

:

15.2 Chemical Safety Assessment This product contains substances for which Chemical Safety Assessments are still

to be received.

# **SECTION 16: Other information**

CEPE code : 2

Indicates information that has changed from previously issued version.

Abbreviations and

: ATE = Acute Toxicity Estimate

acronyms

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

## Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification			Justification
Not classified.			
Full text of abbreviated H	• H302	Harmful if swallowed	

Full text of abbreviated H statements

i nouz namilium swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H330 Fatal if inhaled. H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Acute Tox. 2, H330
 Acute Tox. 4, H302
 Acute Tox. 4, H312
 Acute Tox. 4, H312
 Acute Tox. 4, H332
 Acute Tox. 4, H332
 Acute Tox. 4, H332
 Acute Tox. 4, H330
 Acute Tox. 4, H331
 Acute Tox. 4, H331
 Acute Tox. 4, H332
 Acute To

Aquatic Chronic 3, H412 AQUATIC HAZARD (LONG-TERM) - Category 3
Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2

Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1
Skin Sens. 1B, H317 SKIN SENSITIZATION - Category 1B

Date of issue : 11 August, 2016 Page: 11/12

### **SECTION 16: Other information**

STOT SE 3, H335

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3

Full text of abbreviated R

phrases

: R22- Harmful if swallowed.

R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.

R34- Causes burns.

R41- Risk of serious damage to eyes.

R38- Irritating to skin.

R43- May cause sensitization by skin contact.

R50- Very toxic to aquatic organisms.

R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Full text of classifications

[DSD/DPD]

: C - Corrosive Xn - Harmful Xi - Irritant

N - Dangerous for the environment

Date of printing : 16 August 2016

Date of previous issue : No previous validation

**Notice to reader** 

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

#### Annex

Date of issue : 11 August, 2016 Page: 12/12